



## **Declaration of Performance**

1 Nr. A000542401

2 Unique identification code of product-type 54

3 Trademark FINEO12: 6 mm Planibel Clearlite Annealed - 0,1 mm vacuum - 6 mm Advanced for FINEO pos.3 Annealed

4 Intended use/es Vacuum insulating glass intended to be used in buildings and construction work
5 Manufacturer AGC Glass Europe - Avenue Jean Monnet 4 - 1348 Louvain-la-Neuve - Belgium

6 European Assessment Document EAD 300021-00-0404

7 European Technical Assessment
 8 Technical Assessment Body
 9 Notified body/ies
 ETA 20/0048
 UBAtc
 1136 1174

## 10 Declared performance/s

ESSENTIAL CHARACTERISTIC	REFERENCE METHOD	PERFORMANCE	AVCP SYSTEM
Reaction to fire	Regulation (EU) 2016/364 <sup>1</sup>	A1	3
Mechanical behavior	EAD 300021/00-0404	Validated <sup>2</sup>	3
Airborne sound insulation performance	ISO 19916-1:2018	Rw (C;Ctr) = $36 (-1;-2) dB$	3
Thermal insulation performance	ISO 19916-1:2018	$Ug = 0.7 \text{ W/m}^2\text{K}$ g = 60%	3
Durability of coated glass	EN 1096-3:2012	Class: C - Pass	3
Durability of vacuum insulated glass unit	EAD 300021/00-0404	Pass	3

<sup>1</sup> Commission Delegated Regulation (EU) 2016/364, without the need for testing on the basis of it fulfilling the conditions set out in Commission Decision 96/603/EC, as amended by Commission Decisions 2000/605/EC and 2003/424/EC.

11 The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) N° 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

(name and function)	At (place) on (date of issue)	(signature)
Daniel D'Hont	Louvain-la-Neuve	1 AAT
Vice President Downstream	28/11/2024	
Architectural Glass Europe		

<sup>&</sup>lt;sup>2</sup> Creep resistance of pillars is validated (see C.2 of EAD 300021-00-0404). Fitness for use (see calculation report).